



KOPPERS
Performance
Chemicals

25
year guarantee

Dindas H3 Treated LVL – Safe as houses

- Offers peace of mind and is guaranteed* against decay and termites
- Does not affect moisture content, grade or glue bonds
- Does not cause corrosion of fixings
- Provides the best option for dimensional stability with no swelling, twisting or delamination

DINDAS
australia

Product and description

Laminated Veneer Lumber (LVL) is a versatile building and construction material. It has many important benefits over alternative materials including cost effectiveness, ease of use and net environmental impact. However, it may require protection from natural agents such as decay and termites. Dindas uses a Light Organic Solvent Preservative (LOSP) system for treatment of our LVL and other engineered wood products. LOSP treatment is preferred as it does not affect the dimensional stability or moisture content of the wood products. The LOSP treatment is colourless and non-corrosive to metal fasteners. We now carry an extensive range of H3 LOSP treated LVL ready for pickup and/or delivery.

Why Dindas H3 Treated LVL?

Dindas LVL treated to Hazard Class H3 is suitable for outside, above ground applications. The range provides the best option for engineered strength, durability and sustainable design and building. Our H3 LOSP treatment provides superior penetration and compliance compared to other H3 treatment processes for LVL. LOSP is the preferred process for H3 treatment of structural timber and engineered wood products in Australia. The best way to ensure durability against decay and termites for LVL products is with our H3 LOSP treatment protection.



Dindas H3 Treated LVL range – LVL13 & E14 (F17)[†]

Product size (mm)	Treatment level
90 x 45	H3 LOSP
140 x 45	H3 LOSP
150 x 45	H3 LOSP
190 x 45	H3 LOSP
200 x 45	H3 LOSP
240 x 45	H3 LOSP
300 x 45	H3 LOSP
360 x 45	H3 LOSP
400 x 45	H3 LOSP
200 x 63	H3 LOSP
240 x 63	H3 LOSP
300 x 63	H3 LOSP
360 x 63	H3 LOSP

[†] Check availability of quantities and lengths prior to ordering

Applications

Dindas H3 Treated LVL is an engineered solution for exposed beams in garages, carports, verandahs, alfresco and entry areas. To get the best performance from your product, refer to the treatment section of our website for additional information on weather exposed applications.

Design and take-off service

We can assist with beam sizing, installation advice and everything in between.

For more information visit dindas.com.au

VICTORIA

58 Whiteside Road, Clayton
Phone 03 8540 0500
Fax 03 8540 0599
Email vicestimating@dindas.com.au

NEW SOUTH WALES

138 Dunheved Circuit, St Marys
Phone 02 9673 8000
Fax 02 9673 8099
Email nswestimating@dindas.com.au

QUEENSLAND

433 Wondall Road, Tingalpa
Phone 07 3249 9888
Fax 07 3249 9899
Email qldestimating@dindas.com.au

DINDAS
australia